

## ALINTEG COMPANY Sidewalk, Floor, Brick, Wall, & Window

#### StreetTRAX® - "ONE-STEP" Outdoor Sidewalk Graphics Vinyl Media Suitable for: Latex, UV-cured, UVgel Solvent and Eco-solvent inkiet printers TEXTURE NO lamination needed! finis Facestoc Outdoor Size Product Family/ Durabili mils Stock Number Description Soll 6 1785.00 STX1528V2PW54L100 Up to 1 yr 54" x 100' 40 13.5 Grit Coated White IFSI 🗹 Aggressive High-tack 928.00 13.5 STX1528V2PW54L50 Up to 1 yr 54" x 50' 23 StreetRAP® - "TWO-STEP" Outdoor Sidewalk Graphics Vinyl Media

Suitable for: Solvent, eco-solvent, latex, UV-cured and UVgel inkjet inks and UV or solvent screen inks.

Laminate with: Outdoor floor graphics must be laminated with PF6654W54L100 slip resistant overlaminating films. 54" x 150 ft. - 1279.00 roll



### Mactac Print and Stick w/ M-Dot removable adhesive

Easy and fast application and removability enabled with the dotted adhesive.

Able to be removed and reapplied. Printability with Solvent - Eco-Solvent - UV - and Latex Printers. No water or application tools required. NO LAMINATION REQUIRED.

MD 199 and MD 228 Designed for indoor WINDOWS and WALLS. - MD128 Designed for INDOOR FLOORS

Product	Roll Size	Gauge	Face	Adhesive	Liner	Indoor Only Durability	Prices
MD199W54L164	54"x164ft.	4.7 mil	Gloss Clear	Dot Patterned Removable	5 mil coated paper	up to 1 year	432.00
MD228W54L164	54"x164ft.	4.7 mil	White Matte	Dot Patterned	2 mil	up to 1 year	424.00
MD128FW54L82	54" x 82ft.	7.9	White Matte	Dot Patterned	74# White kraft	up to 6months	353.00

# by MACtac



251122

Application: Wall Graphics Material: RoughRAP\*\*

### Specialty | Solvent-based, UV Cured Ink Jet Media

IMAGin<sup>®</sup> RoughRAP<sup>™</sup> is a 2.1-mil soft white gloss, highly conformable PVC film designed for solvent-based ink jet printing. The product is coated on one side with a high-tack, permanent, opaque acrylic adhesive. RoughRAP is specifically designed for direct application onto exterior and interior brick walls for a painted on look. Use of an overlaminate will extend the life of the graphic and allow for easier handling during installation.

No lamination

### Features and Benefits:

- 2.1-mil highly conformable vinyl face
- High-tack, permanent adhesive 80# polycoated liner for excellent
- printability and layflat Superior print quality for vibrant
- images
- Typical Uses:

Exterior and interior brick walls Roll 54"x 75ft. - 719.00 RR100W54L75 Roll 54"x150ft.-1398.00 RR100W54L150

Physical Properties		Typical Values	
Peel Adhesion, lb./in. 180° on Stainless Steel	- 24 hr	3.2-5.0	
Quick Tack on SS, lb./in2	_	4.8-6.2	
Dimensional Stability (shri 48 hours @ 158°F (70°C)	inkage), %	max 0.5	
Temperature Ranges Minimum Application: End Use:	50°F (+10°C) -4° to 150°F (-20° to 70°C)		
Shelf Life: Two years from D.O.M when 50% relative humidity in th			

