

# SCREEN AND FRAME MAKING AIDS

## KIWOBOND Frame Adhesives

### KIWOBOND 1000 HMT

A fast drying two-component adhesive for adhering mesh to wood, aluminum, and metal frames. 1000 HMT is the choice for high mesh tension and fast drying requirements. The low viscosity aids the application on very fine mesh counts, ideally above 305 tpi (120 tpcm). Not recommended for mesh counts below 156 tpi (60 tpcm). Technical sheet available.



1000HMT-750 Gram Set (adhesive & hardener)	54.85
1000HMT-4.25 Kilo Set (adhesive & hardener)	231.30
1000HMT-4.25 Kilo Frame Adhesive only	149.75
1000HMT-1 Kilo Hardener only	81.55



**KIWOBOND 930 SET**

### KIWOBOND 930

A fast drying two-component adhesive for adhering mesh to wood, aluminum, and metal frames. Its medium viscosity enables easy application even on the coarsest mesh counts. Recommended for mesh counts below 260 tpi (100 tpcm) Technical Sheet available.

**KIWOBOND 930 Set - 52.15**

## FOLDING MAGNIFIER For all Meshes

Fine Quality magnifier. Precision ground polished lens. Magnifies fabric threads. 12X. Folds up for easy storage



**1" - 24.95**

## AUTOTYPE EXPOSURE CALCULATOR

An all-in-one test positive that helps you determine the best exposure time. The calculator's series of incremental gray neutral filters provides 5 exposure values with just one test exposure. Select one of them for the best stencil thickness, colour/hardness and definition. Features include a 65 line screen ruling and halftone dots in 10, 50 and 90% areas. Also the edge definition/resolution targets have a break in them and very fine type to assist your interpretation. A complete instruction guide is provided with each calculator.



**92.00 ea.**

## SOLVENT RESISTANT Plastic Tape

Durable, white polyethylene reinforced cloth tape is pressure sensitive...has tremendous tack. Perfect for sealing off inside of frames, protecting edges and guides, etc. Molds into all crevices and corners and is simply removed. Tape is 2" wide and comes in 60 yard rolls.

**2" x 60 yd. - 26.75**



## FABRIC PREP

### ULANO GEL 23

An abrasive degreaser gel that combines the actions of Microgrit No. 2 and Screen Degreaser Liquid No. 3

The abrading action of Ulanogel 23 promotes better wetting of the fabric and adhesion of the stencil, and thus, longer press life. Its degreasing action removes dirt, dust, and oils from the fabric, reducing the risk of stencil failure and pinholing. Ulanogel 23 is ready-to-use and rinses off in hot or cold water. Its thixotropic character permits easy and effective preparation of larger screens held in a vertical position. Non-caustic - will not harm frames, fabric, or adhesives on stretch and glue frames. Recommended for use with all stencil systems on synthetic fabric only.



**Gallon - 62.00**

### UNIVERSAL MESH-PREP

A non toxic fluid for degreasing and dramatically improving the wetting characteristics of all mesh types. Universal Mesh Prep is fast and easy to apply and harmless to the mesh. Developed for capillary films but suitable for all stencil systems.



**5 Litre (1.32 gal.) Containers 68.00**



### ULANO #3 SCREEN DEGREASER LIQUID

A degreaser solution for all fabrics new or used, before stencil making - and as a degreaser after ink removal to speed the action of the stencil removal. Ready to use. No mixing. Foam action cleaning. Degreases effectively in hard water. Rinses clean with hot or cold water. Non caustic.

**Quart - 16.25  
Gallon - 46.00**



# Adhesives & Additives



**SPRAY ADHESIVES AND CEMENT**



## ®WELD-ON® CEMENT WELD-ON #16

Fast-setting, medium bodied, high strength acrylic cement. Also bonds rigid PVC, ABS, styrene, butyrate, polycarbonate to themselves and each other, as well as other plastics and porous surfaces. **5oz. tube - 11.50 ea.**



### SPRAYWAY 66 SPRAY ADHESIVE

Tacks down T shirts and other fabrics to the pallet. Will not transfer to the fabric. Easily removed with Sprayway C 60 Solvent Cleaner. Used for layouts, display assembly, labelling, etc. Quick tack - Non Wrinkling. Water resistant. Repositionable. **11 oz. 10.75**

## SPRAY ADHESIVES



### PREMIUM MIST ADHESIVE

- Super Strong Tack
- Stable at High Temperatures
- Less Frequent Re-application
- Great for Screen Printing uses.
- Premium Mist Spray applies more adhesive solids for obtaining a strong bond while using less adhesive.
- Great in applications where a light mist adhesive does not provide enough tack.
- Premium Mist Adhesive is heat stable, water resistant, presents a fast tack and will not wrinkle most porous surfaces or fabrics. **14 oz. - 7.95**



### SPRAYWAY 83 WEB TYPE SPRAY ADHESIVE

A quick drying translucent tack adhesive that provides temporary holding of textile fabrics to the printing pallet. Printing can follow immediately after application. After printing, fabric strips quickly without staining. **15 oz - 8.65**



### 3M Super 77

**Multi-Purpose Spray Adhesive** with high coverage and high tack. Use for bonding light weight materials, felt, and carpeting to plastics, foam, painted and unpainted wood, glass, metals, and much more.

**467 g (16.5 oz.) 21.95**



### Methylene Chloride

A bonding agent for acrylics/plexiglass. Sold in 3 different size metal containers. **Quart - 19.50**  
**Gallon - 48.50**

## APPLICATOR SYRINGE



For applying methylene chloride and other solvent cements to: Acrylic, Plexiglas, Lucite, and Acrylite. 1/2 oz. squeeze bottle with 27 ga. needle. **6.25 ea.**

## 3M™ Edge Sealer



Use this product to seal exposed edges of compatible films to help prevent the film from lifting due to environmental exposure or cleaning. **1/2pt. dauber tin - 29.95**



## 203 Masking Tape

**3M™ General Purpose**  
Built on a foundation of innovation, it sticks to many surfaces and removes cleanly with no residue.



**The Standard of the Industry**

60 yd rolls

WIDTH	PRICE	CASE	PRICE
	Part Case		Full Case
3/4"	1.95	48	1.75
1"	2.40	36	2.15
1 1/2"	3.65	24	3.35
2"	4.50	24	4.25

### 3M™ TAPE PRIMER 94

3M Tape Primer 94 can be used to promote adhesion of tapes to difficult surfaces such as: polyethylene, polypropylene, ABS, PET/PBT blends, concrete, wood, glass, metal and painted metal surfaces. **-1/2 pt. tin - 22.95**



### 3M™ Overlamine 8914 Tape



**Designed for use on Window Perforated Graphic Films.** Provides optically clear graphic protection and prevents **moisture** and **contamination** from collecting on **base film's perforations**. Used as an edge sealer where a film type sealer is needed. **-Rolls 1/2" x 75 ft. - 9.60 ea.**