

# Adhesives & Additives

## ® WELD • ON ® CEMENT



Fast-setting, medium bodied, high strength acrylic cement. Also bonds rigid PVC, ABS, styrene, butyrate, polycarbonate to themselves and each other, as well as other plastics and porous surfaces. **5 oz. tube 14.95**



### SPRAYWAY 82 MIST TYPE SPRAY ADHESIVE

Created for textile screen printers who specialize in T-shirts and similar materials. Bonds easily to cloth, paper, cardboard, acetate, foil, plastic film, cork, foam rubber, and leather. Pressure-sensitive formula is repositionable without losing strength. Will not transfer to fabric or allow shifting during screen printing process.

**13 oz. 12.30**



### SPRAYWAY 83 WEB TYPE SPRAY ADHESIVE

A quick drying translucent tack adhesive that provides temporary holding of textile fabrics to the printing pallet. Printing can follow immediately after application. After printing, fabrics strips quickly without staining.

**13 oz - 11.75**



### Methylene Chloride

A bonding agent for acrylics/plexiglass. Sold in metal containers.



### APPLICATOR SYRINGE

For applying methylene chloride and other solvent cements to: Acrylic, Plexiglas, Lucite, and Acrylite. 1/2 oz. squeeze bottle with 27 ga. needle. **7.95 ea.**

## 3M™ Edge Sealer 3950

**1/2pt. Dauber Tin 35.75**



Includes felt application dauber  
Do not apply directly to painted surfaces

3M™ Edge Sealer can be applied around exposed edges of compatible films to help prevent the film from lifting due to environmental exposure or cleaning.

3M™ Edge Sealer helps minimize the adverse effects of rigorous use or prolonged or severe exposure conditions by providing water and contaminant tight seal between a graphic film and substrate.

### 3M™ TAPE PRIMER 94

3M™ Tape Primer 94 can be used to promote adhesion of tapes to difficult surfaces such as: polyethylene, polypropylene, ABS, PET/PBT blends, concrete, wood, glass, metal and painted metal surfaces. -1/2 pt. tin - 32.95



### 3M™ Overlaminata 8914 Tape

**Designed for use on Window Perforated Graphic Films.** Provides optically clear graphic protection and prevents moisture and contamination from collecting on base film's perforations. Used as an edge sealer where a film type sealer is needed. **Rolls 1/2" x 75 ft. - 16.75 ea.**

